COUNTY COUNCIL OF PRINCE GEORGE'S COUNTY, MARYLAND 2025 Legislative Session

Bill No. CB-035-2025									
Chapter No.									
Proposed and Presented by Council Member Ivey									
Introduced by									
Co-Sponsors									
Date of Introduction									
BILL									
AN ACT concerning									
Universal Design for Housing - 2025 Revisions									
For the purpose of removing and re-lettering certain definitions; providing for revisions to									
certain design elements; providing for a certain clearance for certain exterior door entrances;									
providing for a certain clearance for certain lead walks; providing for a certain clearance for									
certain hallways on the accessible level; providing for a certain clearance for certain doorways									
on the accessible level; providing for a certain clearance for certain interior hallways in									
townhouse and two-over-two units; providing for a certain clearance for certain interior									
doorways in townhouse and two-over-two units; and generally regarding Universal Design									
elements for certain newly constructed residential housing dwelling units.									
BY repealing and reenacting with amendments:									
SUBTITLE 4. BUILDING.									
Sections 4-356, 4-358, 4-359, and 4-364,									
The Prince George's County Code									
(2023 Edition; 2024 Supplement).									
SECTION 1. BE IT ENACTED by the County Council of Prince George's County,									

Maryland, that Sections 4-356, 4-358, 4-359 and 4-364 of the Prince George's County Code be

and the same are hereby repealed and reenacted with the following amendments:

1	SUBTITLE 4. BUILDING.
2	DIVISION 6. UNIVERSAL DESIGN FOR HOUSING.
3	Sec. 4-356. Universal Design: Definitions.
4	[(a)] [Accepted by the Maryland-National Capital Park and Planning Commission
5	means an application that is submitted and accepted by the Department of Permitting,
6	Inspections and Enforcement and distributed to all agencies for review.]
7	[(b)] (a) Accessibility means a site, building, facility, or portion thereof that complies with
8	the ADA Standards for Accessible Design ADA.gov, IRC requires compliance with IBC
9	chapter 11 when 4 or more dwellings. International Residential Code (IRC) - CHAPTER 3
10	(iccsafe.org), and IBC – meet all of chapter 11, INTERNATIONAL BUILDING CODE (IBC)
11	ICC DIGITAL CODES (iccsafe.org).
12	[(c)] (b) Accessible Range - For reach ranges, ADAAG 308.1, there is forward reach, side
13	reach. ADA Standards for Accessible Design ADA.gov
14	[(d)] (c) Accessible Route - Accessible routes shall comply with Chapter 4. 2010 ADA
15	Standards for Accessible Design ADA.gov, and IBC – a continuous, unobstructed path that
16	complies with chapter 11.
17	[(e) Approved by the Maryland-National Capital Park and Planning Commission
18	refers to accepted by the building official, per the IRC.]
19	[(f)] (d) Disability is a physical condition that limits a person's movements, senses, or
20	activities.
21	[(g)] (e) Dwellings covered by the design requirements means that the public or
22	common use areas of the building can be approached, entered, and used by individuals with
23	physical disabilities.
24	[(h)] (f) Knobs - handles require more grip strength to grab and turn the handle.
25	[(i)] (g) Levers - handles can be more easily used regardless of the user's grip strength as
26	levers can be pushed.
27	[(j)] (h) Site Impracticality means of evaluating individual buildings and sites with
28	difficult terrain.
29	[(k)] (i) Site plan, for purposes of this Division, shall include a permit site plan, a detailed
30	site plan, a specific design plan, and a special permit site plan.
31	[(l)] (j) Slip Resistant Floors mean accessible surfaces must be slip resistant to minimize

hazards to people with disabilities, especially those who are ambulatory or semi-ambulatory or who use canes, crutches, and other walking aids. Flooring designed with material properties to help reduce slipperiness and increase traction.

- [(m)] (k) **Two-over-two's "Dwelling, two-family,"** is a building containing two dwelling units. For the purpose of this Division, two-over-two's are units stacked one above the other in a vertical configuration, sharing common vertical solid walls extending from the grade to the roof, or horizontal floors and ceilings. The building typologies commonly referred to as two-over-two dwellings or stacked dwelling units are examples of two-family dwellings.
- [(n)] (1) Universal Design is the design of buildings, products, or environments so that they can be accessed, understood, and used to the greatest extent possible by all people regardless of their age, size, ability, or disability.
- [(o)] (m) **Usability** [refers to the ease of access and/or uses within and around a dwelling unit.] means the public or common use areas of the building can be approached, entered, and used by individuals with physical disabilities.

* * * * * * * * *

Sec. 4-358. Universal Design: Exterior/Entrance.

- (a) There shall be a step-free route of travel to at least one step-free entrance to the dwelling unit. Entrance to the unit by way of a garage would qualify as an acceptable route. Multifamily dwelling units located within a building that are above the first floor of the building and are only accessible via stairway are exempt from this requirement.
- (b) The door of this entrance shall [be] <u>have</u> a minimum of 36-inches [-wide] <u>clearance</u> and shall meet all applicable building requirements.
- (c) Exterior lead walks shall be structurally firm and slip resistant with a smooth uniform surface.
- (d) Lead walks shall [be] <u>have</u> a minimum of 42-inch [wide] <u>clearance</u> from the point of arrival to the primary or garage entrance and any slope should be consistent with all applicable requirements.

Sec. 4-359. Universal Design: Interior Accessible Route.

- (a) At least one accessible route shall connect all spaces and elements that are a part of the accessible entry level floor of the dwelling unit.
 - (b) The kitchen shall be on the accessible level and on the accessible route.

- (c) Hallways on the accessible level shall have a 42-inch [-wide] minimum clearance [width] measured from wall to wall.
- (d) Doorways on the accessible route shall have a minimum door [width of] <u>clearance</u> of 36-inches and all doors shall contain levers for accessible access.
- (e) Interior thresholds with levels which exceed ¼-inch high, shall be beveled, with a slope not steeper than one-inch rise to a 2-inch run (1:2).
- (f) Accessible routes shall have flooring that allows resistance-free use of a wheelchair or similar mobility aid or device.
- (g) At least one separate room on the accessible entry level floor of the dwelling unit shall include architectural or design features that include but are not limited to a door that closes and a window to ensure egressibility.

* * * * * * * * * *

Sec. 4-364. Townhouses; Two-Over-Two's, Applicable Universal Design Requirements.

Notwithstanding the exemptions set forth in Section 4-357(f) and Section 4-357(g) of this Division, only the following universal design requirements in this Division shall be required for townhouses and two over two's:

- (a) Universal Design: Interior Hallways, Doorways, Stairs.
- (1) Hallways shall have a 42-inch [-wide] minimum clearance [width] measured from wall to wall.
- (2) Doorways shall have a minimum [width] <u>clearance</u> of 36-inches and all doors shall contain levers for accessible access.
- (3) Interior stairs shall be able to accommodate the installation of a chair lift, with an electrical outlet within four feet of the stairs.
 - (b) Universal Design: Bathroom.
- (1) Continuous wall reinforcement at toilet and bathroom fixtures shall be included to enable easy retrofitting with grab bar(s). All wall reinforcement shall be capable of resisting shear and bending forces of a minimum of 250 pounds.
- (2) Controls on sinks, tubs, showers, and toilets shall be easily accessible or usable by persons with disabilities.
- (c) Universal Design: Smoke Detectors and Fire and Carbon Monoxide Alarms. Audible and visual smoke detectors, fire alarms, and carbon monoxide alarms shall be installed pursuant

1	to the IBC.									
2	* * *	*	*	*	*	*	*			
3	SECTION 2. BE IT FURTHER ENACTED that the provisions of this Act are hereby									
4	declared to be severable; and, in the event that any section, subsection, paragraph, subparagraph,									
5	sentence, clause, phrase, or word of this Act is declared invalid or unconstitutional by a court of									
6	competent jurisdiction, such invalidity or unconstitutionality shall not affect the remaining									
7	words, phrases, clauses, sentences, subparagraphs, paragraphs, subsections, or sections of this									
8	Act, since the same would have been enacted without the incorporation in this Act of any such									
9	invalid or unconstitutional word, phrase, clause, sentence, paragraph, subparagraph, subsection,									
10	or section.									
	SECTION 3. BE IT	FURTHER ENA	ACTED t	hat this A	ct shall ta	ke effect for	ty-five (45)			
	calendar days after it become	mes law.								
	Adopted this da	y of	, 2025	5.						
					NCIL OF P JNTY, MA	PRINCE ARYLAND				
		BY	:				_			
			Edward Counci	l P. Burro l Chair	ughs, III					
	ATTEST:									
	Donna J. Brown Clerk of the Council		APPRO	OVED:						
	DATE:	BY	:							
				. Jackson County E	xecutive					