COUNTY COUNCIL OF PRINCE GEORGE'S COUNTY, MARYLAND 2015 Legislative Session

Bill No.	CB-36-2015
Chapter No.	
Proposed and F	resented by The Chairman (by request – County Executive)
Introduced by	Council Members Franklin, Turner and Davis
Co-Sponsors	
Date of Introdu	ction June 2, 2015
	BILL
AN ACT concer	ning
	Erosion and Sediment Control and Stormwater Management
For the purpose	of updating the County's erosion and sediment control regulations to be
consistent with t	he State of Maryland's revised erosion sediment control regulations and the
2011 Maryland	Standards and Specifications for Soil Erosion and Sediment Control (Standards
and Specificatio	ns), as adopted by the Maryland Department of Environment in January 2012,
and incorporatin	g by reference the Prince George's County Stormwater Design Manual.
BY repealing an	d reenacting with amendments:
	SUBTITLE 32. WATER RESOURCES
	PROTECTION AND GRADING CODE.
	Sections 32-105, 32-124, 32-125, 32-126, 32-127,
	32-132, 32-141, 32-142, 32-143, 32-144, 32-145,
	32-152, 32-153, 32-170, 32-171, 32-172, 32-175,
	32-178, 32-179, 32-180, 32-182, 32-190, and 32-191
	The Prince George's County Code
	(2011 Edition; 2014 Supplement).
SECTION	1. BE IT ENACTED by the County Council of Prince George's County,
Maryland, that S	ections 32-105, 32-124, 32-125, 32-126, 32-127, 32-132, 32-141, 32-142,
32-143, 32-144,	32-145, 32-152, 32-153, 32-170, 32-171, 32-172, 32-175, 32-178, 32-179,
32-180, 32-182,	32-190, and 32-191 of the Prince George's County Code be and the same are
hereby repealed	and reenacted with the following amendments:

1 2

SUBTITLE 32. WATER RESOURCES PROTECTION AND GRADING CODE. DIVISION 1. ADMINISTRATIVE PROVISIONS.

SUBDIVISION 2. GENERAL PROVISIONS.

Sec. 32-105. Administration; Permits; Expiration of Permits; Correction of Code Violations and Suspension or Revocation and Reissuance of Permits.

(a) Any permit issued for grading pursuant to this Subtitle shall be issued only for a period of time reasonably necessary to perform the work[, a period not to exceed 5 years], as defined in Section 32-143. Where a permit is issued, extended, reissued, renewed or reinstated to correct a violation, the permit shall not exceed ninety (90) days. The initial period of the permit shall be established by the Director based upon the extent of the work required to correct the violation. The permit may be extended or renewed beyond the ninety (90) days, only if the violations have been corrected, [for an additional period of] in one-year increments if, in the opinion of the Director, the applicant has demonstrated substantial progress to complete the work in accordance with the permit and has demonstrated substantial justification for failure to complete the work within the period of the permit. The Board of Appeals shall have no authority to grant an extension to the period of the permit.

* * * * * * * * *

- (c) A permit under which no work is commenced within one hundred eighty (180) days after issuance shall expire and become null and void; provided, however, that the Director may extend the time, as defined in Section 32-143, [not to exceed an additional one hundred eighty (180) days] upon sufficient justification shown.
- (d) A permit under which work has been started and later suspended or discontinued shall expire and become null and void six (6) months after the work has stopped. Work will be considered suspended when the permittee fails to prosecute the work so as to ensure completion within a reasonable period of time.

* * * * * * * * * *

(f) When a permit has expired for failure to commence work, it may be extended, renewed, reissued or reinstated within a period of [thirty (30) days from the date of expiration] 60 days prior to the permit expiration date, if the project conditions are in substantial compliance with this subtitle and State law under which the permit was originally issued. A written request and payment of required renewal or extension fees must be received sixty (60 days) prior to the

1	permit ex
2	further d
3	than two
4	*
5	
6	
7	Sec. 32-1
8	The
9	prevent e
10	economi
11	woodlan
12	and to w
13	which th
14	Division
15	Annotate
16	State of 1
17	the water
18	(COMA)
19	Specifica
20	reduce th
21	physical,
22	property.
23	<u>The</u>
24	of the Ar
25	apply to
26	provision
27	and shall
28	Sec. 32-1
29	(a)
30	this Divi

<u>permit expiration date.</u> A fee shall be collected for each renewal, <u>reissuance or reinstatement</u>, <u>as further defined in Section 32-143.</u> [; provided, however, that no permit shall be renewed more than two (2) times.]

* * * * * * * * * *

DIVISION 2. GRADING, DRAINAGE AND [POLLUTION CONTROL] EROSION AND SEDIMENT CONTROL.

Sec. 32-124. Purpose.

The purpose of this Division is to prevent property damage, protect living resources and prevent environmental degradation to safeguard the public's health, safety, welfare and economic well-being by establishing minimum requirements for grading, reforestation, woodland conservation, drainage, erosion control and pollution discharge and control on land and to watercourses within Prince George's County, Maryland, and to establish procedures by which these requirements are to be administered and enforced. It is the further purpose of this Division to implement the provisions of the [Environment Article-Title 4, Subtitle 1 of the Annotated Code of Maryland, so as to safeguard the natural resources of the County and of the State of Maryland by controlling erosion and sediment deposition on lands and in waters within the watersheds of the State and to prevent their pollution.] Code of Maryland Regulations (COMAR) 26.17.01, the 2011 Maryland Standards and Specifications (Standards and Specifications) and the Stormwater Act of 2007 (Act). Implementing this Ordinance will help reduce the negative impacts of land development on water resources, maintain the chemical, physical, and biological integrity of streams, and minimize damage to public and private property.

The provisions of this Ordinance pursuant to Title 4, Subtitle 1 of the Environment Article of the Annotated Code of Maryland are adopted under the authority of the County Code and shall apply to all land grading occurring within the County. The application of this Ordinance and the provisions expressed herein shall be the minimum erosion and sediment control requirements and shall not be deemed a limitation or repeal of any other powers granted by State statute.

Sec. 32-125. Definitions.

- (a) Wherever the following words are used in, or in conjunction with, the administration of this Division, they shall have the following meaning:
 - (1) Act. Maryland Stormwater Act of 2007.

1	(2) Administration. Maryland Department of the Environment (MDE) Water
2	Management Administration (WMA).
3	(3) Adverse impact. Any deleterious effect on waters or wetlands, including their
4	quality, quantity, surface area, species composition, aesthetics, or usefulness for human or
5	natural uses, which are or may potentially be harmful or injurious to human health, welfare,
6	safety or property, biological productivity, diversity, or stability or that unreasonably interfere
7	with the enjoyment of life or property, including outdoor recreation.
8	[(1)] (4) Afforestation. The establishment of a biological community of perpetual
9	woodlands either through the planting of trees in an area from which trees have always or very
10	long been absent, or planting of open areas which are not presently in forest cover.
11	[(2)] (5) Agricultural Land Management Practices. Those methods and
12	procedures used in the cultivation of land in order to further crop and livestock production and
13	conservation of related soil and water resources. Logging and/or timber harvesting operations
14	shall not be considered a part of this definition.
15	(6) Applicant. Any person, firm, or government agency that executes the necessary
16	forms to apply for a permit or approval to carry out construction of a project.
17	(7) Approval authority. The entity responsible for the review and approval of
18	erosion and sediment control plans is the Prince George's Soil Conservation District.
19	[(3)] (8) ASTM. The American Society for Testing Materials.
20	[(4)] (9) Bedrock . The solid undisturbed rock in place either at the ground surface or
21	beneath surficial soil deposits.
22	(10) Best management practice (BMP). A structural device or nonstructural practice
23	designed to temporarily store or treat stormwater runoff in order to mitigate flooding, reduce
24	pollution, and provide other amenities.
25	[(5)] (11) Borrow Pit. The source of earth or bank-run sand and gravel from below
26	the ground surface by open pit excavation as a single incident on a site for use at a single
27	construction site elsewhere, otherwise, the excavation will be classed as open-pit mining.
28	[(6)] (12) Building Pad. The immediate site for a building including the area actually
29	covered, plus the adjacent peripheral fringe area having a reasonable slope away from the
30	building.

- [(7)] (13) **Certification or to Certify.** A signed written statement that specific plans and specifications, construction, inspections, or tests have been prepared and performed, and that such comply with the requirements of this Division.
- [(8)] (14) Chesapeake Bay Critical Area. All waters of and lands under the Chesapeake Bay and its tributaries to the head of tide as indicated on the State wetlands' maps; and all State and private wetlands designated under the Annotated Code of Maryland, Natural Resources Article, Title 9; and all land and water areas within one thousand (1,000) feet beyond the landward boundaries of State or private wetlands and heads of tide designated under the Annotated Code of Maryland, Natural Resources Article Title 9, as indicated on approved Chesapeake Bay Critical Area Overlay Zoning Map Amendments.
- [(9)] (15) Class I Fill. Load-bearing fills proposed for support of buildings, walls and other structures, the function thereof which would be especially impaired by settlement.
- [(10)] (16) Class 2 Fill. Load-bearing fills proposed for support of roadways, pavements, rigid utility lines, house connections, and structures which would not be especially impaired by moderate settlement.
- [(11)] (17) Class 3 Fill. Common fills proposed for lawns, landscape plantings, or for other nonload-bearing usage.
- (18) Clear. To remove vegetation and the vegetative ground cover while leaving the root mat intact.
- [(12)] (19) **Compaction.** Densification of soil or rock fills by mechanical or other acceptable procedures.
- (20) Concept plan. The first of three plans submitted under the comprehensive review and approval process required by the Act and described in COMAR 26.17.02 and shall include the information necessary to allow an initial evaluation of a proposed project.
- [(13)] (21) **Conservation Agreement.** A formal agreement which commits a grading or building permit applicant to the execution of various approved elements of a Conservation Plan, including a stormwater management concept plan, an erosion and sedimentation concept plan, a vegetation management plan, and other plans which may be required by the Department of Permitting, Inspections, and Enforcement or the Prince George's County Planning Board.
- [(14)] (22) **Conservation Plan.** A plan developed in accordance with Subtitle 5B, which demonstrates how a project has been designed to meet the specific Critical Area

1	Commission criteria. The Conservation Plan consists of an approved stormwater management
2	concept plan, an approved sediment and erosion control plan, a vegetation management plan, and
3	such other plans relating to environmental systems as may be required by the Washington
4	Suburban Sanitary Commission, the Maryland-National Capital Park and Planning Commission,
5	the Prince George's County Health Department, the Department or the Prince George's Soil
6	Conservation District.
7	[(15)] (23) Control Measures. Structural or nonstructural devices or practices, or a
8	combination thereof, which reduce pollutant discharges through control, treatment, prevention,
9	management or monitoring measures and processes.
10	(24) County. Prince George's County Government.
11	[(16)] (25) Cultivation. Plowing, dicing, harrowing and tilling of existing farm fields
12	for the production of crops and livestock.
13	[(17)] (26) Department. Department of Permitting, Inspections, and Enforcement.
14	[(18)] (27) Director . The Director of the Department of Permitting, Inspections, and
15	Enforcement or the Director's designee.
16	[(19)] (28) Discharge. Any dumping, pumping, placement, storage, use, draining,
17	handling, washing, tracking, spilling, leaking, transportation, conveyance or disposal practice or
18	any other mechanism which may result in or may allow pollutants to enter onto land or within
19	the watercourses of the County.
20	[(20)] (29) Drainage. Stormwater runoff, snow melt runoff, surface runoff or ground
21	water flows.
22	(30) Drainage area. That area contributing runoff to a single point measured in a
23	horizontal plane that is enclosed by a ridge line.
24	[(21)] (31) Drainage System. Any natural system or man-made device, mechanism or
25	measure used in any manner for the collection, conveyance, management, treatment, disposition
26	or disposal of drainage.
27	[(22)] (32) Dust Free Surface. A ground composed of rolled and compacted cinders,
28	gravels or other approved nonabsorbent materials to prevent rising of dust on roads, access ways,
29	driveways and parking lots.
30	[(23)] (33) Embankment of Fill. A deposit of soil, rock or other materials placed by
31	man.

1	[(24)] (34) Engineering Geology. The application of geological data and principles to
2	engineering problems dealing with naturally occurring rock and soil, for the purpose of assuring
3	that geological factors are recognized and adequately interpreted in engineering practice.
4	(35) Environmental Site Design (ESD). Using small-scale stormwater management
5	practices, nonstructural techniques, and better site planning to mimic natural hydrologic runoff
6	characteristics and minimize the impact of land development on water resources.
7	[(25)] (36) Erosion. The process by which the ground surface is worn away by the
8	action of wind [and/or], water, ice, or gravity.
9	(37) Erosion and sediment control. A system of structural and vegetative measures
10	that minimizes soil erosion and off-site sedimentation.
11	[(26)] (38) Erosion and Sediment Control Plan. An erosion and sediment control
12	strategy or plan, designed to minimize erosion and prevent off-site sedimentation [by containing
13	sediment on site or by passing sediment laden runoff through a sediment control measure,
14	prepared and approved in accordance with the specific requirements of the Prince George's Soil
15	Conservation District and this Subtitle, and designed in accordance with the Standards and
16	Specifications].
17	[(27)] (39) Excavation or Cut. An act, by which soil or rock is cut into, dug, quarried,
18	uncovered, removed, displaced or relocated and shall include the conditions resulting therefrom.
19	(40) Exemption. Those land development activities that are not subject to the erosion
20	and sediment control requirements contained in this Ordinance.
21	[(28)] (41) Existing Grade. The vertical location of the existing ground surface prior
22	to excavating or filling.
23	(42) Final Erosion and Sediment Control Plan. The last of three (3) erosion and
24	sediment control plans submitted under the comprehensive review and approval process required
25	by the Act and described in COMAR 26.17.02. Final erosion and sediment control plans shall be
26	prepared and approved in accordance with the specific requirements of the Prince George's Soil
27	Conservation District and this Ordinance and designed in accordance with the Standards and
28	Specifications.
29	[(29)] (43) Finished or Proposed Grade. The final grade or elevation of the ground,
30	drainage or other structures conforming to the proposed design.

1	[(30)] (44) Forest Stand Delineation (FSD). A detailed accounting of woody
2	vegetation prepared in plan and document form, as required by Subtitle 25.
3	[(31)] (45) Grading. Any stripping, removal of topsoil, excavating, filling,
4	stockpiling, grubbing, removing root mat or any combination thereof, including the condition
5	resulting therefrom.
6	[(32)] (46) Grading Permit. A permit issued to authorize work to be performed under
7	this Division. The permit for grading and/or site development intended as an incident to building
8	construction may be included as part of the building permit.
9	(47) Grading unit. The maximum contiguous area allowed to be graded at a given
10	time. For the purposes of this Ordinance, a grading unit is 20 acres or less.
11	(48) Highly erodible soils. Those soils with a slope greater than 15 percent or those
12	soils with a soil erodibility factor K, greater than 0.35 and with slopes greater than 5 percent.
13	(49) Inspection Agency. Means the Administration or, if delegated enforcement
14	authority, Prince George's County.
15	[(33)] (50) Landscape Architect. A person duly registered or authorized to practice
16	landscape architecture in the State of Maryland and qualified to prepare grading plans and
17	specifications.
18	[(34)] (51) Load-Bearing Fill. Fill placed in a controlled manner to support structure
19	foundations, vehicular traffic, or any earthwork which the instability thereof would constitute a
20	public hazard or nuisance.
21	(52) Maximum extent practicable (MEP). Designing stormwater management
22	systems so that all reasonable opportunities for using ESD planning techniques and treatment
23	practices are exhausted and only where absolutely necessary is a structural BMP implemented.
24	[(35)] (53) Mitigation. The offsetting of forest values lost due to the destruction of
25	woodlands without a permit or contrary to an approved Tree Conservation Plan by replanting
26	woodlands or agreed upon means.
27	[(36)] (54) Natural Ground Surface . The ground surface in its original state before
28	any grading, excavation or filling.
29	[(37)] (55) Net Tract Area. For the purposes of woodland conservation, the gross
30	tract area minus the approved one hundred (100) year floodplain and areas previously dedicated
31	for public use.
l	

1	[(38)] (56) One Hundred (100) Year Floodplain. That area which would be
2	inundated by a flood that has a one percent (1%) chance of being equaled or exceeded in any
3	given year.
4	[(39)] (57) Open-Pit Mining. The continuing or reoccurring removal of material from
5	below the ground surface by open excavation on a site for immediate or ultimate use at the same
6	or other site in processing and manufacturing of building and construction materials or any other
7	products, or at various locations elsewhere in its natural state.
8	(58) Owner/Developer. A person undertaking, or for whose benefit activities covered
9	by this Ordinance are carried on. General contractors or subcontractors, or both, without a
10	proprietary interest in a project are not included within this definition.
11	[(40)] (59) Permittee. Any person to whom a permit is issued pursuant to this
12	Division.
13	(60) Person. Includes the federal government, the State, any county, municipal
14	corporation, or other political subdivision of the State, or any of their units, or an individual,
15	receiver, trustee, guardian, executor, administrator, fiduciary, or representative of any kind, or
16	any partnership, firm, association, public or private corporation, or any of their affiliates, or any
17	other entity.
18	[(41)] (61) Pollutant. Sediment runoff due to erosion.
19	[(42)] (62) Ponding. Water that remains on the ground surface in a single area larger
20	than sixteen (16) square feet for more than forty-eight (48) hours after a rain event where cold
21	weather conditions (such as, but not limited to, frozen ground or combined ice, snow or rain
22	event) are not a contributing factor in water remaining on the ground surface.
23	[(43)] (63) Prince George's Soil Conservation District. One (1) of twenty four (24)
24	soil conservation districts created pursuant to Subtitle 3 of the Agricultural Article of the
25	Annotated Code of Maryland.
26	[(44)] (64) Professional Engineer. A person duly registered or otherwise authorized
27	by the State of Maryland to practice in the field of engineering.
28	[(45)] (65) Reforestation. The re-establishment of a biological community of
29	perpetual woodlands through the planting of trees on areas from which trees were recently
30	removed.
31	[(46)] (66) Refuse. See "solid wastes (refuse)."

1	(67) Responsible personnel. Any foreman, superintendent, or project engineer who is	
2	in charge of on-site clearing and grading operations or the implementation and maintenance of an	
3	erosion and sediment control plan.	
4	[(47)] (68) Sediment. Soils or other surficial materials transported or deposited by	
5	[surface water as a product of erosion] the action of wind, water, ice, gravity, or artificial means.	
6	[(48)] (69) Significant Drainage. Surface drainage rates that exceed three (3) cubic	
7	feet per second based on the ten (10) year storm event as calculated by the Rational Method.	
8	[(49)] (70) Site. [Any lot or parcel of land combination of contiguous lots or parcels of	
9	land.] Any tract, lot, or parcel of land, or combination of tracts, lots or parcels of land that are in	
10	one ownership, or are contiguous and in diverse ownership, where development is to be	
11	performed as part of a unit, subdivision, or project.	
12	[(50)] (71) Site Development. The resulting condition of land improvements through	
13	the constructing, installing, placing or planting of: open and closed storm drainage facilities,	
14	stormwater management facilities, supporting foundations for utility lines and service (house)	
15	connections, parking lots, driveways, curbs, pavements, steps, sidewalks, bike paths, recreational	
16	facilities, patios, ground planters, ground covers, plantings, landscaping and logging and timber	
17	harvesting operations.	
18	(72) Site Development Plan. The second of three (3) plans submitted under the	
19	comprehensive review and approval process required by the Act and described in COMAR	
20	26.17.02. A site development plan shall include the information necessary to allow a detailed	
21	evaluation of a proposed project.	
22	[(51)] (73) Slope. The inclined exposed surface of a fill, excavation or natural terrain.	
23	[(52)] (74) Soil. All earth material of whatever origin that overlies bedrock and may	
24	include the decomposed zone of bedrock which can be readily excavated by mechanical	
25	equipment.	
26	[(53)] (75) Soil Engineer. A professional engineer who is qualified by education and	
27	experience to practice applied soil mechanics and foundation engineering.	
28	[(54)] (76) Solid Wastes (Refuse). The same as defined in Subtitle 21 of this Code.	
29	(77) Stabilization. The protection of exposed soils from erosion by the application of	
30	seed and mulch, seed and matting, sod, other vegetative measures, and/or structural means.	
31	[(55)] (78) Standards and Specifications. [The current version of the "Maryland	

1	Standards and Specifications for Soil Erosion and Sediment Control as adopted by the Prince
2	George's Soil Conservation District.] The "2011 Maryland Standards and Specifications for Soil
3	Erosion and Sediment Control" and any subsequent revisions.
4	(79) Stormwater. Water that originates from a precipitation event.
5	(80) Stormwater Management System. Natural areas, ESD practices, stormwater
6	management measures, and any other structure through which stormwater flows, infiltrates, or
7	discharges from a site.
8	[(56)] (81) Stripping. Any activity which removes or significantly disturbs the
9	vegetation surface cover including clearing, grubbing of stumps and root mat and top soil
10	removal.
11	[(57)] (82) Structural Rock Fills. Fills including limited amounts of rubble, broken
12	asphalt, brick or concrete.
13	[(58)] (83) Surveyor. A registered land surveyor licensed to practice land surveying in
14	the State of Maryland and qualified to prepare grading plans and specifications.
15	[(59)] (84) Timber Harvesting (Logging). The severing of any size tree above
16	ground level leaving the root system and all stumps intact, except for the purpose of providing a
17	temporary access for some other use, or for the removal of a dead, dying or hazardous tree. A
18	Tree Conservation Plan may be required for the timber harvesting activities to be conducted in
19	conformance with Subtitle 25.
20	[(60)] (85) Topsoil. Soil to be used as topsoil, and the placement of topsoil over a
21	prepared subsoil prior to the establishment of permanent vegetation, shall meet the specifications
22	of, and be in accordance with, Maryland Department of the Environment, Standards and
23	Specifications for Soil Erosion and Sediment Control, [21.0] <u>B-4-2</u> Standards and Specifications
24	for [Topsoil or approved subsequent revisions thereof] soil preparation, and soil amendments.
25	[(61)] (86) Tree Conservation Plan (TCP). A site map that delineates woodland
26	conservation areas and the associated text that details requirements, penalties, and mitigation as
27	described in Subtitle 25.
28	(87) Variance. The modification of the minimum erosion and sediment control
29	requirements for exceptional circumstances such that strict adherence to the requirements would
30	result in unnecessary hardship and not fulfill the intent of this Ordinance.
31	[62)] (88) Watercourse. Any natural or improved stream, river, creek, ditch, channel,

1	canal, conduit, curvert, drain, guily, swale or wash in which waters flow either continuously or
2	intermittently.
3	(89) Watershed. The total drainage area contributing runoff to a single point.
4	Sec. 32-126. Permits Required.
5	(a) Grading Permit. Except as exempted in Section 32-127, no person shall do, nor shall
6	the property owner permit any site development or grading of land for any purpose without the
7	owner/permittee of the said land first having obtained a grading permit from the Director.
8	Before a grading permit for any site is issued by the County, the Prince George's Soil
9	Conservation District must review and approve an erosion and sediment control plan for the site.
10	* * * * * * * * *
11	(h) No person shall disturb land without implementing soil erosion and sediment controls
12	in accordance with the requirements of this Ordinance and the Standards and Specifications
13	except as provided within this Section.
14	Sec. 32-127. Exceptions to Grading Permit.
15	(a) Provided all other provisions of this Division are met and excluding the property
16	located within the Chesapeake Bay Critical Area Overlay Zone, no grading or storm drain
17	connection permit will be required under the following conditions:
18	* * * * * * * * *
19	(6) Grading, as a maintenance measure, or for landscaping or construction purposes
20	on existing developed lots or parcels, provided:
21	(A) The aggregate of area(s) affected or bare-earthed at any one (1) time does
22	not exceed five thousand (5,000) square feet or disturb less than 100 cubic yards of earth;
23	(B) The grade change does not exceed twelve (12) inches at any point and does
24	not alter the drainage pattern;
25	(C) All bare earth is promptly seeded, sodded or otherwise effectively protected
26	from erosive actions.
27	(D) Does not require a Tree Conservation Plan per Subtitle 25.
28	* * * * * * * * *
29	Sec. 32-132. Waiver <u>and Variances</u> .
30	* * * * * * * * *
31	[(b) The Prince George's Soil Conservation District may grant a written waiver from the

1	requirements of the Standards and Specifications if strict adherence to the specifications will
2	result in unnecessary hardship and not fulfill the intent of this Subtitle. The applicant shall
3	submit a written request for a waiver to the Prince George's Soil Conservation District. The
4	request shall state the specific waiver sought and reasons for requesting the variance. The Prince
5	George's Soil Conservation District shall not grant a waiver unless and until sufficient specific
6	reasons justifying the waiver are provided by the applicant.]
7	(b) Erosion and Sediment Control Variances: The Prince George's Soil Conservation
8	District may only grant a variance from the requirements of the Standards and Specifications
9	when strict adherence will result in unnecessary hardship and not fulfill the intent of this
10	Ordinance. The owner/developer shall submit a written request for a variance to the Prince
11	George's Soil Conservation District. The request must state the specific variance sought and the
12	reasons for the request. The Prince George's Soil Conservation District shall not grant a
13	variance unless and until sufficient information is provided describing the unique circumstances
14	of the site to justify the variance.
15	* * * * * * * * *
16	Sec. 32-141. Enforcement Action Upon Noncompliance.
17	* * * * * * * * *
18	(e) Erosion and Sediment Control Enforcement
19	(1) The County shall, through the authority of this Ordinance and COMAR 26.17.01
20	use enforcement action when erosion and sediment control violations occur.
21	(2) Enforcement actions may include, but are not limited to:
22	(A) <u>Issuance of a corrective action order;</u>
23	(B) Issuance of a stop work order, the extent of which is determined by the
24	County:
25	(C) Issuance of a penalty or fine as allowed; and
26	(D) Referral for legal action.
27	(3) The County may deny the issuance of any permits to an applicant when it
28	determines that the applicant is not in compliance with the provisions of a building or grading
29	permit or approved erosion and sediment control plan.
30	(4) The County shall stop work on a site where land disturbance is occurring without
31	an approved erosion and sediment control plan, if not otherwise exempt. Measures shall be

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30

required to be implemented to prevent off-site sedimentation.

(f) Severability: If any portion, section, subsection, sentence, clause, or phrase of this Ordinance is for any reason held invalid or unconstitutional by any court of competent jurisdiction, such portion shall be deemed a separate, distinct, and independent provision and such holding shall not affect the validity of the remaining portion of this Ordinance, it being the intent of the County that this Ordinance shall stand, notwithstanding the invalidity of any portion, section, subsection, sentence, clause, or phrase, hereof.

(g) Penalties

- (1) Any person who violates any provision of this Ordinance is guilty of a misdemeanor, and upon conviction in a court of competent jurisdiction is subject to a fine not exceeding \$10,000 or imprisonment not exceeding one year or both for each violation with costs imposed in the discretion of the court. Each day upon which the violation occurs constitutes a separate offense.
- (2) Any agency whose approval is required under this Ordinance or any interested person may seek an injunction against any person who violates or threatens to violate any provision of this Ordinance.
- (3) In addition to any other sanction under this Ordinance, a person who fails to install or to maintain erosion and sediment controls in accordance with an approved plan shall be liable to County or the State in a civil action, for damages in an amount equal to double the cost of installing or maintaining the controls.
- (4) Any governing authority that recovers damages in accordance with this subsection shall deposit them in a special fund, to be used solely for:
- (A) Correcting to the extent possible the failure to implement or maintain erosion and sediment controls; and
 - (B) Administration of the sediment control program.

32-142. [Changes to Plans] <u>Modifications to Approved Erosion and Sediment Control Plans</u>.

[(a) All changes or modifications to the approved grading plans must be submitted to and approved by the Director. All necessary substantiating reports shall be submitted with any proposal to modify the approved grading plans. No grading or other work in connection with any proposed modification shall be permitted without the prior written approval of the Director.]

- [(b) When inspection of a site indicates that the approved erosion and sediment control plan needs change, the change shall be in compliance with the erosion and sediment control criteria contained in the Standards and Specifications as follows:]
- [(1) The permittee shall submit requests for major revisions to approved erosion and sediment control plans, such as the addition or deletion of a sediment basin, to the Prince George's Soil Conservation District to be processed appropriately. This processing includes revisions due to plan and site discrepancies and inadequacies controlling erosion and sediment as revealed through inspection; major revisions affecting the limits of disturbance shall require a revised Tree Conservation Plan; and]
- [(2) The Director may approve minor modifications to approved erosion and sediment control plans in the field if documented on a field inspection report. The modification shall be noted on the approved plans, signed by an inspector and dated. The Prince George's Soil Conservation District, shall in conjunction with the Department of Permitting, Inspections, and Enforcement, develop a list of allowable field modifications for use by field inspection personnel; minor revisions resulting in less than 5,000 square feet of vegetation removal per site may be verified.]
- (a) The Prince George's Soil Conservation District may require the revision of approved plans as necessary. Modifications may be requested by the owner/developer, the inspection agency, or the County in accordance with COMAR 26.17.01.09(H) Plan Modifications.
- (b) The Prince George's Soil Conservation District shall develop a list of minor modifications that may be approved as field revisions by the inspection agency. The Administration shall review and approve any list of minor modifications prior to its implementation.

Sec. 32-143. Time Limits.

(a) Generally. [No grading or drainage system connection permits shall be issued for a period to exceed 5 years.] Grading or drainage system connection permits shall be issued for a period not to exceed two (2) years where the estimated cost of work is less than Five Hundred Thousand Dollars (\$500,000.00) and for a period not to exceed three (3) years where the estimated cost of work is equal to or more than Five Hundred Thousand Dollars (\$500,000.00). The permittee shall fully perform and complete all of the work shown on the plans within the time limit specified in the permit.

-	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	

- (b) Extension. Prior to the expiration of a grading permit, the permittee may present a written request for an extension to the Director. If[, in the opinion of the Director] an extension is warranted, [a one-time extension, not to exceed one (1) year may be granted] it may be granted in one year increments, one year at a time. Extension fees shall be calculated at the same rate as permit fees, and based on the amount of site area that has not received final inspection approval. Extension fees for road construction included in a grading permit shall be calculated in accordance with Section 23 of the County Code. The applicability of bonding requirements shall be adjusted accordingly. Application for permit renewal and extension shall be made at least sixty (60) days prior to the permit expiration date.
- (c) <u>Permit Expiration and Renewal.</u> <u>Application for permit renewal and extension shall be</u> made at least sixty (60) days prior to the permit expiration date.
- (d) Extension beyond 6 years. If, in the opinion of the Director, a permit extension beyond six (6) years is warranted, it may be granted in one year increments. Such extensions require justification from the permittee and approval by the Director of the Department of Permitting, Inspections and Enforcement.
- (e) No Activity. If no site work and/or no site inspections have occurred in a six (6) month period, the County may, in its sole discretion, default or close the permit.

Sec. 32-144. Inspection and Supervision.

- (a) The Director <u>or his designee</u> shall inspect all work and shall require that the permittee furnish adequate supervision, documentation of satisfactory testing and compaction prepared and certified by a professional engineer duly registered in the State of Maryland for all Class 1, Class 2 and Class 3 fills as deemed necessary.
- (b) [Prior to the] <u>After the</u> issuance of a grading permit, the permittee, the contractor and/or their agents shall attend a preconstruction meeting on-site with the Director <u>or his</u> <u>designee</u> on each site requiring an approved sediment and erosion control plan.

* * * * * * * * *

- (e) The owner/developer shall maintain a copy of the approved erosion and sediment control plan on site.
- (f) Every active site having an approved erosion and sediment control plan should be inspected for compliance with the plan on average, once every two (2) weeks.
 - (g) The County shall notify the on-site personnel or the owner/developer in writing when

1	violations are observed, describing:
2	(1) The nature of the violation;
3	(2) The required corrective action; and
4	(3) The time period in which to have the violation corrected.
5	(h) Right of Entry: It shall be a condition of every grading or building permit that the
6	County has the right to enter property periodically to inspect for compliance with the approved
7	plan and this Ordinance.
8	(i) Complaints: The County shall accept and investigate complaints regarding erosion and
9	sediment control concerns from any interested parties and:
10	(1) Conduct an initial investigation within three (3) working days from receipt of the
11	complaint;
12	(2) Notify the complainant of the initial investigation and findings within seven (7)
13	days from receipt of the complaint; and
14	(3) Take appropriate action when violations are discovered during the course of the
15	complaint investigation.
16	(j) For inspection and enforcement of the woodland conservation program and the erosion
17	and sediment control program, the following shall be required:
18	(1) Ensure that approved tree conservation plans and approved Erosion and Sediment
19	Control plans and permits are on the site and are complied with;
20	(2) Ensure that every active site having an erosion and sediment control plan is
21	inspected for compliance with the approved plan on the average of once every two weeks; and
22	(3) Prepare written reports after every inspection that describe:
23	(A) The date and location of this site inspection;
24	(B) Whether the approved plan has been properly implemented and maintained;
25	(C) Practical deficiencies or erosion and sediment control plan deficiencies; and
26	(D) If a violation exists, the type of enforcement action that is taken.
27	(E) If applicable, a description of any modifications to the plan.
28	Section 32-145. Reports.
29	* * * * * * * * *
30	(b) Prepare written reports after every inspection that describe:
31	(1) The date and location of this site inspection;
I	

1	<u>(2)</u>	Wheth	er the approv	ved plan has	s been prop	erly implen	nented and	maintained:	• <u>•</u>
2	<u>(3)</u>	Practic	al deficienci	es or erosic	n and sedir	nent contro	l plan defic	iencies;	
3	<u>(4)</u>	If a vio	lation exists	, the type o	f enforceme	ent action th	at is taken	; and	
4	<u>(5)</u>	If appli	cable, a des	cription of a	any modific	cations to th	e plan.		
5	*	*	*	*	*	*	*	*	*
6	Sec. 32-152.	Ground	Stabilizati	on.					
7	(a) All	graded s	urfaces shal	l have suita	ble soil for	permanent	vegetative	growth; free	e of
8	any rocks, sto	ones or o	ther nonirred	lucible/non	organic ma	tter larger tl	nan one and	d one-half (1 ½)
9	inches in dia	meter; [d	iced] <u>disked</u>	and raked;	and shall b	e limed, fer	tilized, seed	ded, mulche	d with
10	tack or sodde	d, plante	d or otherwi	se protected	d from eros	ion; and sha	ıll be water	ed, tended a	and
11	maintained u	ntil grow	th is well es	tablished.					
12	(1)	Topsoi	l shall be in	accordance	with the M	laryland De	partment of	f the	
13	Environment	, Standar	ds and Spec	ifications fo	or Soil Eros	ion and Sed	liment Con	trol, [21.0]	B-4-2
14	Standard and	Specific	ations for [T	opsoil,] <u>To</u>	psoiling an	d soil amen	dments or a	approved	
15	subsequent re	evisions t	hereof.						
16	(2)	Stabiliz	zation metho	ds and mat	erials shall	be in accord	dance with	the Marylai	nd
17	Department of	of the En	vironment, S	standards ar	nd Specifica	ations for E	rosion and	Sediment C	ontrol,
18	[20.0] <u>B-4-4</u> ,	B-4-5, S	tandards and	d Specificat	ions for [V	egetative St	abilization] Temporar	y and
19	Permanent St	tabilizatio	on, or appro	ved subsequ	ent revisio	ns thereof.			
20	*	*	*	*	*	*	*	*	*
21	Sec. 32-153.	Content	ts <u>, Review a</u>	nd Approv	<u>al</u> of the E	rosion and	Sediment	Control Pl	an.
22	*	*	*	*	*	*	*	*	*
23	(b) <u>At</u>	<u>a minimu</u>	<u>ım,</u> [A] <u>a</u> ppli	cants shall	submit the	following ir	formation	to the Princ	e
24	George's Soi	1 Conserv	vation Distri	ct:					
25	(1)	A lette	r of transmit	tal <u>and/or a</u>	pplication l	known as a	site analysi	<u>s</u> ;	
26	(2)	A vicir	nity sketch ir	ndicating no	orth arrow,	scale and ot	her informa	ation necess	sary to
27	easily locate	the prope	erty;						
28	[(3)) A plan	at an approp	oriate scale	indicating a	at least:]			
29		[(A) N	ame, addres	s and teleph	one numbe	er of:]			
30		[(i) The owne	r of the pro	perty where	the grading	g is propos	ed;]	
31			[(aa) Th	ne applicant	;]				
l	l								

1	[(B) The existing and proposed topography;]
2	[(C) The proposed grading and earth disturbance including:]
3	[(i) Surface area involved;]
4	[(ii) Excess spoil material;]
5	[(iii) Use of borrow material;]
6	[(iv) Specific limits of disturbance consistent to that shown on an approved
7	Type 2 Tree Conservation Plan; and]
8	[(v) A clear and definite delineation of all woodland conservation areas and
9	areas to remain undisturbed consistent with the approved Type 2 Tree Conservation Plan;]
10	[(D) Storm drainage provisions, including:]
11	[(i) Velocities and quantities of flow at outfalls; and]
12	[(ii) Site conditions around points of all surface water discharge from the
13	site;]
14	[(E) Erosion and sediment control provisions to minimize on-site erosion and
15	prevent off-site sedimentation including:]
16	[(i) Provisions to preserve top soil and limit disturbance;]
17	[(ii) Details of grading practices;]
18	(3) Drainage area map(s) showing existing, interim, and proposed topography,
19	proposed improvements, standard symbols for proposed sediment control features, and pertinent
20	drainage information including provisions to protect downstream areas from erosion for a
21	minimum of 200 feet downstream or to the next conveyance system;
22	(4) The location of natural resources, wetlands, floodplains, highly erodible soils,
23	slopes 15 percent and steeper, and any other sensitive areas;
24	(5) A general description of the predominant soil types on the site, as described by
25	the appropriate soil survey information available through the Prince George's Soil Conservation
26	District or the USDA Natural Resources Soils Conservation Service;
27	(6) Proposed stormwater management practices;
28	(7) An Erosion and sediment control plan at an appropriate scale, including at least:
29	(A) Name, address and telephone number of:
30	(i) The owner of the property where the grading is proposed;
31	(<u>ii</u>) <u>The applicant; and</u>

1		<u>(iii)</u>	The developer.	
2	<u>(B)</u>	The	existing topography and improvements as well as proposed topography	
3	and improvements at a scale between 1" = 10' and 1" = 50' with 2 foot contours or other			
4	approved contour in	nterva	<u>ıl;</u>	
5	(<u>C</u>)	Scal	e, project and sheet title, and north arrow on each plan sheet;	
6	<u>(D)</u>	The	proposed grading and earth disturbance including:	
7		<u>(i)</u>	Total disturbed area;	
8		<u>(ii)</u>	Volume of cut and fill quantities;	
9		<u>(iii)</u>	Volume of borrow and spoil quantities;	
10		<u>(iv)</u>	Specific limits of disturbance consistent to that shown on an approved	
11	Type 2 Tree Conse	rvatio	on Plan; and	
12		<u>(v)</u>	A clear and definite delineation of all woodland conservation areas and	
13	areas to remain und	listurt	ped consistent with the approved Type 2 Tree Conservation Plan;	
14	<u>(E)</u>	Scal	e, project and sheet title, and north arrow on each plan sheet;	
15	(F) The limit of disturbance (LOD) including:			
16		<u>(i)</u>	Limit of grading (grading units, if applicable); and	
17		<u>(ii)</u>	Initial, interim, and final phases;	
18	<u>(G)</u>	Stor	m drainage features, including:	
19		<u>(i)</u>	Existing and proposed bridges, storm drains, culverts, outfalls, etc;	
20		<u>(ii)</u>	Velocities and quantities of peak flow rates at outfalls for the two-year	
21	and ten-year freque	ncy s	torm events; and	
22		<u>(iii)</u>	Site conditions around points of all surface water discharge from the	
23	site;			
24	<u>(H)</u>	Eros	tion and sediment control practices to minimize on-site erosion and	
25	prevent off-site sed	iment	tation including:	
26		<u>(i)</u>	The salvage and reuse of top soil;	
27		<u>(ii)</u>	Phased construction and implementation of grading unit(s) to minimize	
28	disturbances, both i	n ext	ent and duration, not to exceed 20 acres;	
29		<u>(iii)</u>	Location and type of all proposed erosion and sediment control	
30	practices;			

1	(<u>iv</u>) <u>Design details and data for all erosion and sediment control practices;</u>
2	<u>and</u>
3	(v) Specifications for temporary and permanent stabilization measures
4	including, at a minimum:
5	a. The "Standard Stabilization Note" on the plan stating: "Following
6	initial soil disturbance or re-disturbance, permanent or temporary stabilization must be
7	completed within:
8	1. Three (3) calendar days as to the surface of all perimeter
9	dikes, swales, ditches, perimeter slopes, and all slopes steeper than 3 horizontal to 1 vertical
10	(3:1); and
11	2. Seven (7) calendar days as to all other disturbed or graded
12	areas on the project site not under active grading."
13	b. Details for areas requiring accelerated stabilization; and
14	c. Maintenance requirements as defined in the Standards and
15	Specifications;
16	[(4)] (8) Design details for structural controls;
17	[(5)] (9) Details of temporary and permanent stabilization measures including
18	placement of the statement on the plan that following initial soil disturbance or redisturbance,
19	permanent or temporary stabilization shall be completed within seven (7) calendar days for the
20	surface of all perimeter dikes, swales, ditches, perimeter slopes and all slopes greater than 3
21	horizontal to 1 vertical (3:1), and for all embankments of ponds, basins and traps; and fourteen
22	(14) days for all other disturbed or graded areas on the project site provided that the requirements
23	of this Section do not apply to those areas which are shown on the plan and are currently being
24	used for material storage or for those areas on which actual construction activities are currently
25	being performed or to interior areas of a surface mine site where the stabilization material would
26	contaminate the recoverable resource;
27	[(6)] $\underline{(10)}$ \underline{A} [S]sequence of construction describing the relationship between the
28	implementation and maintenance of controls, including permanent and temporary stabilization
29	and the various stages or phases of earth disturbance and construction. Any changes or revisions
30	to the sequence of construction must be approved by Prince George's Soil Conservation District

1	<u>prior to proceeding with construction.</u> The sequence of construction shall, at a minimum,
2	include a schedule and time frame for the following [activities]:
3	(A) Request for a pre-construction meeting with the Department;
4	[(A)](B) Clearing and grubbing for those areas necessary for installation of
5	perimeter controls;
6	[(B)](C) Construction and stabilization of perimeter controls within installed
7	perimeter controls;
8	[(C)](D) Remaining clearing and grubbing;
9	[(D)](E) Road grading;
10	[(E)](F) Grading for the remainder of the site;
11	[(F)](G) Utility installation and [whether storm drains will be used or blocked
12	after construction] connections to existing structures;
13	(H) Construction of buildings, roads, and other construction;
14	[(G)](I) Final grading, landscaping [or] and stabilization;
15	[(H) Removal of controls;]
16	(J) Construction of building roads and other construction;
17	(K) Installation of stormwater management measures;
18	(L) Approval of the appropriate enforcement authority prior to removal of
19	sediment controls; and
20	(M) Removal of controls and stabilization of areas that are disturbed by removal
21	of sediment controls.
22	[(7)] (11) A statement placed on the plan indicating that the [permittee]
23	owner/developer or representative shall request that the Department of Permitting, Inspections,
24	and Enforcement or its agent approve work completed in accordance with the approved erosion
25	and sediment control plan, the grading or building permit, and this Division, and that the
26	[permittee] owner/developer or representative shall obtain written inspection approvals by the
27	Director or his designee at the following stages in the development of the site, or of each
28	subdivision thereof:
29	(A) Prior to the start of earth disturbance;
30	[(A)](B) Upon completion of installation of tree protection devices, followed by
31	the installation of perimeter erosion and sediment controls, prior to proceeding with any other

1	earth disturbance or grading. Other building or grading inspection approvals may not be
2	authorized until initial approval by the Department is made;
3	[(B)](C) Upon completion of stripping, the stockpiling of top soil, the
4	construction of temporary sediment and erosion control facilities, disposal of all waste material
5	and preparation of the ground;
6	[(C)](D) Upon completion of rough grading, but prior to placing top soil,
7	permanent drainage or other site development improvements and ground covers;
8	(E) Prior to the start of another phase of construction or opening of another
9	grading unit;
10	(F) Prior to the removal of sediment control practices; and
11	[(D)](G) Upon completion of final grading, reforestation, permanent drainage,
12	and erosion control facilities including established ground covers and planting, and all other
13	work of the building permit;
14	[(8)] (12) Certification by the owner/developer or permittee that any clearing, grading,
15	construction or development, or all of these, will be done pursuant to [this plan] the approved
16	erosion and sediment control plan. The certification must also require [and] that responsible
17	personnel involved in the construction project will have a Certification of Training at a State of
18	Maryland Department of the Environment approved training program (i.e. Green Card
19	Certification) for the control of sediment and erosion before beginning the project. The
20	Certification of Training for Responsible Personnel requirement may be waived by the Prince
21	George's Soil Conservation District on any project involving four (4) or fewer residential units[;
22	and]. Additionally, the owner/developer shall allow right of entry for periodic on-site evaluation
23	by the Prince George's Soil Conservation District, the Department, and/or MDE; and
24	(13) Certification by a professional engineer, land surveyor, landscape architect (only
25	for plans with no hydraulic and hydrologic calculations), or forester (for forest harvest operations
26	only) registered in the State that the plans have been designed in accordance with erosion and
27	sediment control laws, regulations, and standards, if required by the Prince George's Soil
28	Conservation District or the Administration.
29	[(9)] (14) In approving the plan, the Prince George's Soil Conservation District may
30	require any additional information or data deemed appropriate and/or may impose such
31	conditions thereto as may be deemed necessary to ensure compliance with the provisions of this

Division, the State Sediment Control Regulations, COMAR 26.17.01, the Standards and Specifications, or the preservation of public health and safety.

- (c) Review and Approval of Erosion and Sediment Control Plans
- (1) A person may not grade land without an erosion and sediment control plan approved by the Prince George's Soil Conservation District if the site is not exempt from these requirements.
- (2) The Prince George's Soil Conservation District shall review erosion and sediment control plans to determine compliance with this Ordinance and the Standards and Specifications prior to approval. In approving the plan, the Prince George's Soil Conservation District may impose such conditions that may be deemed necessary to ensure compliance with the provisions of this Ordinance, COMAR 26.17.01, the Standards and Specifications, and the preservation of public health and safety.
- (3) The review and approval process shall be in accordance with the comprehensive and integrated plan approval process described in the Standards and Specifications, Prince George's County Stormwater Ordinance, and the Act.
- (4) At a minimum, a concept plan must include the mapping of natural resources and sensitive areas including highly erodible soils and slopes greater than 15 percent as well as information required under Prince George's County Stormwater Ordinance. These areas are to remain undisturbed or an explanation must be included with either the concept or site development plan describing enhanced protection strategies for these areas during construction. Approved concept sediment control plans remain valid for three (3) years from the date of approval unless extended or renewed by the Prince George's Soil Conservation District.
- (5) A site development plan submittal must include all concept plan information and indicate how proposed erosion and sediment control practices will be integrated with proposed stormwater management practices. The latter is being done through a narrative and an overlay plan showing both ESD and erosion and sediment control practices. An initial sequence of construction and proposed project phasing to achieve the grading unit restriction should be submitted at this time. Approved site development sediment control plans remain valid for three (3) years from the date of approval unless extended or renewed by the Prince George's Soil Conservation District.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30

- (6) An applicant shall submit a final erosion and sediment control plan to the Prince George's Soil Conservation District for review and approval. The plan must include all of the information required by the concept and site development plans as well as any information in Section 32-153.
- (7) A final erosion and sediment control plan shall not be considered approved without the inclusion of the signature and date of signature of the Prince George's Soil Conservation District on the plan.
- (8) Final erosion and sediment control plans remain valid for two (2) years from the date of approval unless extended or renewed by the Prince George's Soil Conservation District.
 - (9) Grandfathering of Approved Plans:
- (A) Any plans that receive final approval after January 9, 2013 must be in compliance with the erosion and sediment control requirements of this Ordinance and the Standards and Specifications.
- (B) A plan that receives final approval by January 9, 2013 may be reapproved under its existing conditions if grading activities have begun on the site by January 9, 2015, with the exception of stabilization requirements.
- (C) Stabilization practices on all sites must be in compliance with the erosion and sediment control requirements of this Ordinance and the Standards and Specifications by January 9, 2013, regardless of when an approved erosion and sediment control plan was approved.
- (d) The erosion and sediment control plan must be designed in concert with a site's stormwater management plan as required by the Stormwater Management Act of 2007 (Act). The Act requires an integrated review of erosion and sediment control plans and stormwater management plans via a comprehensive plan review process to ensure that environmental site design (ESD) is implemented to the maximum extent practicable (MEP) on all sites.
 - (e) Standard Erosion and Sediment Control Plan
- (1) The Prince George's Soil Conservation District may adopt a standard erosion and sediment control plan for activities with minor earth disturbances, such as single-family residences, small commercial and other similar building sites, minor maintenance grading, and minor utility construction.

1	(2) A standard erosion and sediment control plan must meet the requirements of this			
2	Ordinance and the Standards and Specifications.			
3	(3) MDE shall review and approve a standard plan prior to its adoption.			
4	DIVISION 3. STORMWATER MANAGEMENT.			
5	SUBDIVISION 1. GENERAL PROVISIONS.			
6	Sec. 32-170. Short Title; Purpose.			
7	* * * * * * * * *			
8	(f) The following referenced documents are necessary to provide appropriate technical			
9	guidance for the planning, design, construction, inspection and enforcement of the provisions of			
10	this Division. These documents are revised periodically and it is incumbent upon property			
11	owners, planners, designers and applicants to use the most current approved versions available.			
12	For purposes of this Division, the following documents are hereby adopted and incorporated by			
13	reference:			
14	(1) The 2000 Maryland Stormwater Management Design Manual, Volumes I and II			
15	Maryland Department of the Environment (April 2000), as amended; and			
16	(2) The current edition of the 2014 Prince George's County Stormwater Management			
17	Design Manual or any subsequent revisions; and			
18	[(2)](3) The USDA Natural Resources Conservation Service Maryland Conservation			
19	Practice Standard Pond Code 378 (January 2000), as amended.			
20	[(3)](4) Adopted Comprehensive Watershed Management Plans:			
21	(A) CR-61-1986 – Piscataway Creek			
22	(B) CR-62-1986 – Henson Creek			
23	Sec. 32-171. Definitions.			
24	(a) For purposes of this Division, the following terms, phrases and words, and their			
25	derivations shall have the meaning given herein:			
26	* * * * * * * * *			
27	(5) Alternative Practice. An environmental site design practice or technique or			
28	structural stormwater management measure that is not found in the Maryland Design Manual and			
29	is proposed during concept plan approval. Alternative practices shall be designed to meet the			
30	criteria in the Maryland Design Manual, meet the minimum requirements specified in Section			
31	32-178 of this Division and be approved by the Administration.			

1	
2	(11) Channel Protection Storage Volume (Cpv). The volume used to design
3	structural management practices to control stream channel erosion. Methods for calculating the
4	channel protection storage volume are specified in the [2000] Maryland [Stormwater
5	Management] Design Manual and the Prince George's County Design Manual.
6	* * * * * * * * *
7	(27) Environmental Site Design (ESD). Using small scale stormwater management
8	practices, nonstructural techniques, and better site planning to mimic natural hydrologic runoff
9	characteristics and minimize the impact of land development on water resources. (Methods for
10	designing ESD practices are specified in the Maryland Design Manual and the Prince George's
11	County Design Manual).
12	* * * * * * * * *
13	(29) Extended Detention. A stormwater design feature that provides gradual release
14	of a volume of water in order to increase settling of pollutants and protect downstream channels
15	from frequent storm events. (Methods for designing extended detention BMPs are specified in
16	the Maryland Design Manual and the Prince George's County Design Manual).
17	* * * * * * * * *
18	(45) Overbank Flood Protection Volume (Qp). The volume controlled by structural
19	practices to prevent an increase in the frequency of out-of-bank flooding generated by
20	development. (Methods for calculating the overbank flood protection volume are specified in the
21	Maryland Design Manual and the Prince George's County Design Manual).
22	* * * * * * * * *
23	(49) Pollutant . Sediment runoff due to erosion.
24	* * * * * * * * *
25	(54) Prince George's County Design Manual. The 2014 Prince George's County
26	Stormwater Management Design Manual or any subsequent revisions that complements the
27	Maryland Design Manual.
28	[(54)] (55) Recharge Volume (Rev). That portion of the water quality volume used
29	to maintain groundwater recharge rates at development sites. (Methods for calculating the
30	recharge volume are specified in the Maryland Design Manual and the Prince George's County
31	Design Manual).

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31

[(55)] (56) **Redevelopment.** Any construction, alteration or improvement performed on sites where existing land use is commercial, industrial, institutional, or multifamily residential and existing site impervious area within the limit of disturbance exceeds 40 percent.

- [(56)] (57) **Retention Structure**. A permanent structure that provides for the storage of runoff and is designed to maintain a permanent pool of water.
- [(57)] (58) **Retrofitting.** The implementation of ESD practices, the construction of structural BMP, or the modification of an existing structural BMP in a previously developed area to improve water quality over current conditions.
- [(58)] (59) **Sediment**. Soils or other surficial materials transported or deposited by the action of wind, water, snow, ice or gravity as a product of erosion.
- [(59)] (60) **Site**. For new development, any tract, lot, or parcel of land or combination of tracts, lots, parcels of land that are in one ownership or are contiguous and in diverse ownership, where development is to be performed as a part of a unit, subdivision or project.
- [(60)] (61) **Site Development Plan.** The second of three required plan approvals that includes the information necessary to allow a detailed evaluation of a proposed project.
- [(61)] (62) **Stabilization**. The prevention of soil movement by any of various vegetative and/or structural means.
 - [(62)] (63) **Stormwater**. Water that originates from a precipitation event.
- [(63)] (64) **Stormwater Management (SWM)**. Using ESD for the collection, conveyance, storage, treatment and disposal of stormwater runoff in a manner to prevent accelerated channel erosion, increased flood damage and/or degradation of water quality.
- [(64)] (65) **Stormwater Management Design Plan**. The set of drawings and other documents that comprise all of the information and specifications for the systems, structures, concepts, and techniques that will be used to control stormwater as required by the approved concept plan and the Maryland Design Manual and the Prince George's County Design Manual.
- [(65)] (66) **Stormwater Management System.** Natural areas, ESD practices, stormwater management measures, and any other structures through which stormwater flows, infiltrates or discharges from a site.
- [(66)] (67) **Stormwater Variance**. The modification of the minimum stormwater management requirements for specific circumstances such that strict adherence to the requirements would result in unnecessary hardship and not fulfill the intent of this Division.

[(67)] (68) Stream Restoration. Restoration and reconstruction of existing	
waterways to maintain the ecological features of the stream, to mitigate stream bed incision	and
stream wall erosion, to preserve the capacity and to enhance the water quality of the stream.	
Stream restoration shall address the following including, but not limited to, intervention and	
installation of measures to repair damages to the stream corridors, hydrology, hydraulics,	
sediment transport, geomorphology, aquatic ecology, fisheries and riparian ecology.	
[(68)] (69) Stripping . Any activity that removes the vegetation surface cover	
including tree removal, clearing, grubbing and storage or removal of topsoil.	
[(69)] (70) Subdivision . The division of a lot, tract or parcel of land into two or r	nore
lots, plots, sites, parcels or other divisions by plat or deed.	
[(70)] (71) Watercourse. Any natural or artificial stream, river, creek, ditch, cha	nnel,
canal, conduit, culvert, drain, waterway, gully, ravine or wash, in and including any adjacen	area
that is subject to inundation from overflow or flood water.	
[(71)] (72) Water Quality Volume (WQv). The volume needed to capture and to	eat
90 percent of the average annual rainfall at a development site. (Methods for calculating the	:
water quality volume are specified in the Maryland Design Manual and the Prince George's	
County Design Manual.)	
[(72)] (73) Watershed. The total drainage area contributing runoff to a single po	nt.
Sec. 32-172. Watershed Management Planning.	
* * * * * * * *	*
(e) A watershed management plan developed for the purpose of implementing differe	nt
stormwater management policies for waivers and redevelopment shall:	
* * * * * * * *	*
(7) Be consistent with the General Performance Standards for Stormwater	
Management in Maryland as found in the Maryland Design Manual and the Prince George's	
County Design Manual; and	
* * * * * * * *	*
Sec. 32-175. Redevelopment.	
(a) Stormwater management plans are required by the Department for all redevelopment	ent,
unless otherwise specified by watershed management plans developed according to this Div	ision.

1	Stormwa	uer manageme	int measure	es must be c	onsistent w	in the Mar	yiand Desig	n Manuai <u>a</u>	<u>na me</u>
2	Prince George's County Design Manual).								
3	(b) All redevelopment designs shall:								
4	(1) Reduce impervious area within the limit of disturbance (LOD) by at least 50								
5	percent a	according to th	e Maryland	d Design Ma	anual <u>and t</u>	he Prince G	eorge's Cou	ınty Design	:
6	Manual;								
7	*	*	*	*	*	*	*	*	*
8	(c)	All redevelop	oment desig	gns approve	d after May	y 4, 2016, sl	nall:		
9		(1) Reduce	impervious	s area within	n the LOD	by 75 perce	ent in accord	ance with the	he
10	Maryland	d Design Man	ual <u>and the</u>	Prince Geo	rge's Coun	ty Design N	<u>//anual;</u>		
11	*	*	*	*	*	*	*	*	*
12	(d)	All redevelop	oment desig	gns approve	d after Mag	y 4, 2019, sl	nall:		
13		(1) Reduce	impervious	s area within	n the LOD	by 100 perc	ent in accor	dance with	the
14	Maryland	d Design Man	ual and the	Prince Geo	rge's Coun	ty Design N	<u>/Ianual;</u>		
15	*	*	*	*	*	*	*	*	*
16	(g)	All redevelop	oment proje	ects shall red	duce existii	ng site storn	nwater runo	ff volume b	y
17	impleme	nting distribut	ed ESD to	the MEP. V	Where cond	litions preve	ent the imple	ementation	of
18	ESD techniques to reduce runoff, the Maryland [Stormwater] Design Manual and the Prince								
19	George's	s County Design	gn Manual	criteria shal	l be impler	mented.			
20	*	*	*	*	*	*	*	*	*
21		Stormwater r	_			_			
22		bance according	_	_	_		-	_	ınual
23	and the F	Prince George'					-		
24	(1)	If the Depart			xisting floo	oding and/or	erosion exi	ist downstre	am of
25		osed developm		-					
26	*	*	*	*	*	*	*	*	*
27				-	•		100-year fr		
28		downstream f	•		with the M	Iaryland De	sign Manua	l and the Pr	ince
29	George's	S County Design							
30		SUBDIVISI					' DESIGN I	PLANS.	
31	Sec. 32-1	178. Minimu	m Stormwa	ater Contro	ol Require	ments.			
ı	l								

	2	
	3	
	4	
	5	
	6	
	7	
	8	
	9	
1	0	
1	1	
1	2	
1	3	
1	4	
1	5	
1	6	
1	7	
1	8	
1	9	
2	0	
2	1	
2	2	
2	3	
2	4	
2	5	
2	6	
2	7	
	8	
2	9	
3	0	
3	1	

- (a) The minimum control requirements established in this Section and the Maryland Design Manual and the Prince George's County Design Manual are as follows:
- (1) Planning techniques, nonstructural practices, and design methods specified in the Maryland Design Manual and the Prince George's County Design Manual shall be used to implement ESD to the MEP. The use of ESD planning techniques and treatment practices must be exhausted before any structural BMP is implemented. Stormwater management design plans for development projects subject to this Division shall be designed using ESD sizing criteria, recharge volume, water quality volume, and channel protection storage volume criteria according to the Maryland Design Manual and the Prince George's County Design Manual. The MEP standard is met when channel stability is maintained, 100% predevelopment groundwater recharge is replicated, non-point source pollution is minimized, and structural stormwater management practices are used only if determined to be absolutely necessary.
- (2) Attenuation of the 2-year, 10-year frequency storm event for downstream erosion exist and/or attenuation of the 100-year frequency storm event for downstream flooding exist are required according to the Maryland Design Manual and the Prince George's County Design Manual and all subsequent revisions when the Department determines that additional stormwater management is necessary because the receiving channel and/or conveyance system are determined inadequate.

* * * * * * * * *

Sec. 32-179. Stormwater Management Measures.

The ESD planning techniques, practices and structural stormwater management measures in this Division and the Maryland Design Manual and the Prince George's County Design Manual shall be used either alone or in combination in a stormwater management design plan. An applicant shall demonstrate that ESD has been implemented to the MEP before the use of a structural BMP is considered in developing the stormwater management design plan.

- (a) ESD Planning Techniques and Practices.
- (1) The following planning techniques shall be applied to MEP according to the Maryland Design Manual and the Prince George's County Design Manual to satisfy the applicable minimum control requirements established in 32-178 of this Division:

* * * * * * * * * *

(2) The following ESD treatment practices shall be designed to MEP according to the

1	Maryland Design Manual and the Prince George's County Design Manual to satisfy the
2	applicable minimum control requirements established in 32-178 of this Division:
3	* * * * * * * * *
4	(3) The use of ESD planning techniques and treatment practices specified in this
5	Section shall not conflict with existing state law or local ordinances, regulations, or policies. The
6	County shall modify planning and zoning ordinances and public works codes to eliminate any
7	impediments to implementing ESD to the MEP according to the Maryland Design Manual and
8	the Prince George's County Design Manual.
9	(b) Structural Stormwater Management Measures.
10	(1) The following structural stormwater management practices shall be designed
11	according to the Maryland Design Manual and the Prince George's County Design Manual to
12	satisfy the applicable minimum control requirements established in 32-178 of this Division:
13	* * * * * * * * *
14	(2) The performance criteria specified in the Maryland Design Manual <u>and the Prince</u>
15	George's County Design Manual with regard to general feasibility, conveyance, pretreatment,
16	treatment and geometry, environment and landscaping, and maintenance shall be considered
17	when selecting structural stormwater management practices.
18	* * * * * * * * *
19	(d) Alternative ESD planning techniques, treatment practices and structural stormwater
20	measures may be used for new development runoff control if they meet the performance criteria
21	established in the Maryland Design Manual and the Prince George's County Design Manual and
22	all subsequent revisions and are approved by the Administration. Practices used for
23	redevelopment projects shall be approved by the Department.
24	* * * * * * * * * *
25	Sec. 32-180. Specific Design Criteria.
26	The basic design criteria, methodologies, and construction specifications, subject to the
27	approval of the Department and the Administration, shall be in accordance with the Maryland
28	Design Manual and the Prince George's County Design Manual. * * * * * * * * * * * * * * * * * * *
29	
30	Sec. 32-182. Stormwater Management Design Plans, Submission Requirements.
31	(a) Concept Plan.
- 1	П

1	I ne ov	vner/appnc	ant snam sut	omit a conc	ept pian tha	ii provides	sufficient if	mormation i	or an
2	initial assess	sment of the	e proposed	project and	whether sto	ormwater n	nanagement	can be pro	vided
3	according to 32-179 of this Division and the Maryland Design Manual and the Prince George's								
4	County Des	ign Manual	l. Plans sub	mitted for	concept app	roval shall	include, bu	t are not lin	nited
5	to:								
6	*	*	*	*	*	*	*	*	*
7	(d) Re	eports subm	nitted for an	approval o	of final storr	nwater ma	nagement p	lans shall in	clude,
8	but are not l	imited to:							
9	*	*	*	*	*	*	*	*	*
10	(3) Hydrold	gic comput	ations of th	e applicable	e ESD and	unified sizi	ng criteria	
11	according to	the Maryl	and Design	Manual <u>an</u>	d the Prince	e George's	County Des	sign Manual	<u>f</u> or
12	all points of	discharge	from the site	e;					
13	*	*	*	*	*	*	*	*	*
14	(e) Co	onstruction	drawings su	ibmitted fo	r final storn	nwater mai	nagement pl	lan approval	l shall
15	include, but	are not lim	ited to:						
16	*	*	*	*	*	*	*	*	*
17	(1	1) A table	showing the	ESD and	unified sizii	ng criteria	volumes req	uired in the)
18	Maryland D	esign Man	ual and the	Prince Geo	rge's Count	ty Design N	<u>Manual;</u>		
19	*	*	*	*	*	*	*	*	*
20	SUB	DIVISION	3. INSPE	CTION, M	1AINTEN A	ANCE AN	D ENFOR	CEMENT.	
21	Sec. 32-190	. Inspectio	on Schedule	e and Repo	orts.				
22	*	*	*	*	*	*	*	*	*
23	, ,						ch BMP and		
24	planning tec	chnique and	I practice at	the stages	of construct	tion specifi	ed in the M	aryland Des	sign
25	Manual <u>and</u>		_	- -		•	· ·		
26	representati	ves, or certi	ified by a pr	rofessional	engineer lic	ensed in th	ne State of N	Maryland. A	At a
27	minimum, a					-	-	-	
28	completion	Č	C,	tablishmen	t of stabiliz	ation, and l	pefore issua	nce of a use	and
29	occupancy p	• • •							
30	*	*	*	*	*	*	*	*	*
31	Sec. 32-191	. Inspection	on Require	ments Dur	ing Constr	uction.			

1	*	*	*	*	*	*	*	*	*
2	(b) T	he Departi	ment may, fo	or enforcer	nent purpos	es, use an	y one or a c	ombination	of the
3	following a	ctions:							
4	*	*	*	*	*	*	*	*	*
5	(4	1) In addi	ition to any	other sanc	tions, a civi	l action or	criminal pr	rosecution 1	may be
6	brought ag	ainst any p	person in vio	olation of t	his Code, th	ne Marylaı	nd Design N	Manual, the	Prince
7	George's C	ounty Des	ign Manual,	or this Div	ision.				
8	*	*	*	*	*	*	*	*	*
9	(d) O	nce constr	uction is cor	nplete, "as	-built" plan	certificatio	n shall be su	ubmitted by	either
10	a profession	nal enginee	er or professi	ional land	surveyor lice	ensed in th	e State of M	laryland to ϵ	ensure
11	that ESD p	lanning tec	hniques, trea	atment prac	ctices, and st	tructural <u>aı</u>	nd non struc	<u>tural</u> stormy	water
12	managemei	nt measure	s and convey	yance syste	ems comply	with the sp	ecifications	contained i	in the
13	approved p	lans. At a	minimum, "	as-built" c	ertification s	hall includ	le a set of dr	awings	
14	comparing	the approv	ed final stor	mwater ma	magement p	lan with w	hat was con	structed. The	he
15	Departmen	t may requ	ire additiona	ıl informati	on.				
16	*	*	*	*	*	*	*	*	*
17	SECT	ION 2. BI	E IT FURTH	IER ENAC	TED that th	e provisio	ns of this Ac	ct are hereby	y
18	declared to	be severab	ole; and, in th	ne event th	at any sectio	n, subsecti	on, paragra	ph, subpara	graph,
19	sentence, c	lause, phra	se, or word	of this Act	is declared i	nvalid or ι	ınconstitutio	onal by a co	urt of
20	competent	jurisdictior	n, such inval	idity or und	constitutiona	ality shall r	not affect the	e remaining	•
21	words, phra	ases, clause	es, sentences	, subparag	raphs, parag	raphs, subs	sections, or	sections of t	this
22	Act, since t	he same w	ould have be	een enacted	l without the	e incorpora	tion in this	Act of any s	such
23	invalid or u	nconstituti	onal word, p	ohrase, clau	ise, sentence	e, paragrap	h, subparag	raph, subsec	ction,
24	or section.								
25	SECT	'ION 3 <mark>.</mark> BI	E IT FURTH	IER ENAC	TED that th	is Act shall	ll take effect	t forty-five ((45)
26	calendar da	we after it !	hecomes law	7					

Adopte	ed this <u>23rd</u>	day of <u>June</u> , 2015	•		
				COUNTY COUNCIL OF PRINCE GEORGE'S COUNTY, MARYLAND	
		В	Y:	Mel Franklin Chairman	
ATTEST:					
Redis C. Flo				APPROVED:	
DATE:		B	Y:	Rushern L. Baker, III	
				County Executive	
[Brackets] i Asterisks **	ndicate lang		ex	cisting law. Code provisions that remain unchanged.	
*	*	* *		* * * *	*